

Investigation of parameter-dependent material characteristics of additively manufactured specimens for data-driven part optimization

Dominic Zettel^{*1,2}, Piotr Breitkopf¹, Pascal Nicolay² and Roland Willmann²

¹ Université de Technologie de Compiègne (UTC), Laboratoire Roberval, FR3272, CS 60319 60203 COMPIEGNE CEDEX, France, piotr.breitkopf@utc.fr, www.utc.fr

² Carinthia University of Applied Sciences (CUAS), Europastraße 4, 9524 Villach, Austria, d.zettel@cuas.at, www.fh-kaernten.at

Key Words: *laser powder bed fusion, data-driven optimization, green computing, multi-physical optimization, tensile strength, temperature gradient, porosity, microstructure*

In the field of Laser Powder Bed Fusion (LPBF), predictive simulation models are not yet available due to the modeling complexity of physical phenomena interacting at different scales [1]. Furthermore, the simulation of even simple structures can lead to high computing costs (model development, CPU, computing time) which hinders the economic interest of a pure simulation approach [2]. The high computing times in turn correlate with a certain CO2 footprint related to the energy consumption, cooling systems, etc. [3].

Another approach of investigating the material characteristics of a printed structure is to involve experimental data as in the spirit of Stainier et al. [4]. Here, the modeling and simulation of all the complex physical phenomena is enriched by data from practical experiments. Our data assimilation approach is illustrated by a test case in which a Design of Experiments (DoE) is executed. Within the DoE, which includes 17 different parameter sets, 5 sets of cylindrical specimens (StrengthAI) were fabricated via Direct Metal Laser Sintering (DMLS). The material characteristics (porosity, tensile strength, Young's modulus and temperature gradient) were investigated using a Scanning Electron Microscope (SEM), a tensile testing machine (Zwick Roell Z020) and a self-designed test setup for measuring thermal properties.

The test results, which were clustered using the k-mean clustering algorithm, show a clear correlation between the modified parameter settings (laser power, laser speed, hatch distance and layer thickness) and the afore mentioned material characteristics. It was also recognized that the printing parameters lead to different kinds of microstructures (brittle, ductile).

The experimental approach represents the first step within the development of design guidelines that could enable multi-physical part optimization without complex simulation models.

REFERENCES

- [1] J. Zhang, Y. Zhang, W. H. Lee, L. Wu, H.-H. Choi and Y.-G. Jung, "A multi-scale multi-physics modeling framework of laser powder bed fusion additive manufacturing process," *metal powder*, Vol. 73, No. 3, ISSN: 0026-0657, pp. 151-157, June 2018.
- [2] The Minerals, Metals & Materials Society (TMS), "Modeling Across Scales: A Roadmapping Study for Connecting Materials Models and Simulations Across Length and Time Scales," The Minerals, Metals & Materials Society (TMS), ISBN 9780692376065, Warrendale, PA 15086, 2015.
- [3] B. Saha, "Green Computing," *International Journal of Computer Trends and Technology (IJCTT)*, volume 14 number 2, ISSN 2231-2803, pp. 46-50, August 2014.
- [4] L. Stainier, A. Leygue and M. Ortiz, "Model-free data-driven methods in mechanics: Material data identification and solvers," *Computational Mechanics*, Springer Verlag, HAL Id: hal-02159717, June 2019.